Dam It™ Soldering Aid Instructions





For Item Codes: 03380 (1/2" to 2" kit) 03382 (1/2" to 1" kit) 03384 (1/2" tool) 03386 (3/4" tool) 03388 (1" tool)

- 03390 (1-1/4" tool)
- 03390 (1-1/4" tool)
- 03394 (2" tool)

- Stops drips that prevent fast soldering.
- Neoprene seal expands as wing nut is turned.
- · Permanent tool replaces plumber's bread.
- Note: Not for use with live systems. Use only on piping when water pressure is shut off.
- 1. Always wear safety glasses.
- Insert the proper size Dam It[™] Soldering Aid all the way through the valve or fitting to put the neoprene bushing away from the high heat. Not doing so shortens the life of the bushing.
- 3. Tighten the Dam It™ Soldering Aid by holding the handle in one hand and turning the wingnut with the other. This will expand the bushing evenly sealing the pipe.
- To replace the neoprene bushing remove the locknut and first washer. Pull off old bushing. Replace the bushing, washer and locknut.
- 5. Lubricate the wingnut after each use.

Reed Manufacturing Company 1425 West 8th Street Erie, PA 16502 USA



Phone: 800-666-3691 or 814-452-3691 Fax: 800-456-1697 or 814-455-1697