

Cold cut large diameter steel, most stainless steel, ductile, and cast iron pipe in close quarters. The low profile design of the LCRC models needs only 4" clearance for up to 16" pipe diameter; only 8" clearance for the RC20 and RC24; and just 11.8" clearance for the **RC30** and **RC36** large diameter pipe cutters. Each cutter is supplied with a slip-on handle that is used to turn the cutter around the pipe in one direction. The handle is also used to tighten the cutter every 1/2 revolution.

Best manual cutters for ductile iron. With good leverage from long handle, pipe snaps off squarely before wheel penetrates halfway through pipe. Cutters have heavy-duty frames.

All sizes use the same cutter wheels: either RCS8-36 for steel and RCI8-30 for ductile and cast iron. RCX wheels cut up to 25/32" wall thickness for steel pipe.

For heavy wall steel and stainless steel, order RCX cutter wheels (03550) and eight RC8-30XR rollers (93222).

ROTARY CUTTERS

		Pipe Capacity			Length		Weight	
Catalog No.	Item Code	Steel**	Cast Iron & Ductile	Actual			3	
	000	Inches- Nom.		Ømm	in	mm	lbs	kg
RC20S*	03240	20 - 22		476 - 572	106	2680	89	40.5
RC20I*	03242		18 - 20	476 - 572	106	2680	89	40.5
RC24S*	03250	24 - 26		584 - 660	111	2807	107	48.6
RC24I*	03252		22 - 24	584 - 660	111	2807	107	48.6
RC30S*†	03260	28 - 34		698 - 864	96	2438	283	128.6
RC30I*†	03262		30	698 - 864	96	2438	283	128.6
RC36S*†	03264	32 - 36		813 - 915	96	2438	295	134.1
*EXCLUSIVE								

†CONVERSION KITS

Catalog No.	Item Code	Converts			
RC30CONV	03267	RC36 to RC30			
RC36CONV	03268	RC30 to RC36			

CLEARANCES

Cat. No.	in	mm
RC20	8.0	204
RC24	8.0	204
RC30	11.8	300
BC36	11 0	300





Rotary™ Cutters & Low Clearance Rotary™ Cutters

45° between handle slots **CLEARANCE**

TRAINING

For heavy wall steel and stainless steel, order RCX cutter wheels (03550) and eight RC8-30XR rollers (93222).

LOW CLEARANCE ROTARY CUTTERS

		Pipe Capacity			Length		Weight		
Catalog No.	Item Code	Steel**	Cast Iron & Ductile					J. 9	
		Inches- Nom.	Inches- Nom.	Ø mm	in	mm	lbs	kg	
LCRC8S*	03309	6 - 8		159 - 246	58	1473	41	18.6	
LCRC8I*	03308		6 - 8	159 - 246	58	1473	41	18.6	
LCRC12S*	03313	10 - 14		266 - 358	61	1549	50	22.7	
LCRC12I*	03312		10 - 12	266 - 358	61	1549	50	22.7	
LCRC16S*	03317	16 - 18		368 - 462	66	1664	60	27.3	
LCRC16I*	03316		14 - 16	368 - 462	66	1664	60	27.3	

*EXCLUSIVE

NOTE: S= includes cutter wheels for steel; I= for cast and ductile iron. Wheels for same size cutters are interchangeable. Recommend only Reed cutter wheels be used with these cutters. Reed wheels are made from high shock-resistant tool steel on computerized (CNC) machines and then precisely heat-treated. This allows for a thinner profile yet stronger blade, so they:

- Cut easier and faster, especially stainless steel and ductile pipe
- · Last much longer
- Provide the best value

LCRC ACCESSORY

To improve use in awkward locations, Reed now offers an angled handle option that allows the user to turn the LCRC cutter from the side of a ditch, using one's body weight, rather than having to turn the cutter from on top.



Catalog No.	Item Code	Converts
BAHANDLE	93177	Angled Handle option for use with LCRC (Low Clearance Rotary Cutters)
★ NEW		





SINCE 1896

Reed Manufacturing Company 1425 West 8th Street Erie, PA 16502 USA

800-666-3691 or 814-452-3691 Fax 800-456-1697 or 814-455-1697



LCRC12 **Low Clearance Rotary Cutter**

Two Adjusting Nuts to Tighten